PROBRANDS

SAFETY DATA SHEET

1. Identification

Product identifier SCRUBS® Graffiti & Spray Paint Remover Towels

Other means of identification

Part Number 90130

Recommended use Graffiti and spray paint remover

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway

Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or

dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective

gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Dimethyl Glutarate		1119-40-0	10 - 20
Propylene Glycol Methyl Ether		107-98-2	10 - 20
Tripropylene Glycol methyl ether		25498-49-1	10 - 20
Acetone		67-64-1	1 - 10
Ethylene Glycol Monobutyl Ether		111-76-2	1 - 10
2-Methyl Butyl Acetate		624-41-9	1 - 3
Dimethyl succinate		106-65-0	1 - 3
Primary Amyl Acetate		628-63-7	1 - 3

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation.

Symptoms may be delayed.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the **General information** material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Specific methods General fire hazards In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

No special precautions are necessary beyond normal good hygiene practices. See Section 8 of the SDS for additional personal protection advice when handling this product.

Methods and materials for containment and cleaning up **Environmental precautions**

Mechanically pick up material and place in a proper container for disposal.

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air C Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
,		1000 ppm	
Ethylene glycol monobutyl ether (CAS 111-76-2)	PEL	240 mg/m3	
0.1101 (0.100 111 70 2)		50 ppm	
Primary Amyl Acetate (CAS 628-63-7)	PEL	525 mg/m3	
•		100 ppm	
Sodium Hydroxide (CAS 1310-73-2)	PEL	2 mg/m3	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
2-Methyl Butyl Acetate (CAS 624-41-9)	STEL	100 ppm	
	TWA	50 ppm	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA	20 ppm	
Primary Amyl Acetate (CAS 628-63-7)	STEL	100 ppm	
	TWA	50 ppm	
Propylene Glycol Methyl Ether (CAS 107-98-2)	STEL	100 ppm	
	TWA	50 ppm	
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
US. NIOSH: Pocket Guide to Chemic	al Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Primary Amyl Acetate (CAS 628-63-7)	TWA	525 mg/m3	
		100 ppm	
Propylene Glycol Methyl Ether (CAS 107-98-2)	STEL	540 mg/m3	
		150 ppm	
	TWA	360 mg/m3	
		100 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Ethylene glycol monobutyl ether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

Can be absorbed through the skin.

Propylene Glycol Methyl Ether (CAS 107-98-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Not normally needed.

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid. Liquid saturated on wipe.

ColorColorless.OdorSweet.

Odor threshold Not available.

pH 6.3

Melting point/freezing point Not available.

Initial boiling point and boiling 212 °F (100 °C)

range

Flash point 62.0 °F (16.7 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%)
Explosive limit - upper (%)

Not available.

Not available.

Not available.

Vapor pressure Vapor density Relative density

> 1 (air = 1) Not available.

Solubility(ies)

Solubility (water)

Miscible.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Decomposition temperature Not available. Not available. Not available.

Other information

Viscosity

Density 8.23

Explosive properties

Oxidizing properties

Not explosive.

Not oxidizing.

Specific gravity

0.98 - 0.97

VOC

28.15 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

 Components
 Species
 Test Results

 Acetone (CAS 67-64-1)
 Acute Inhalation

 LC50
 Rat
 50 mg/l, 8 Hours

 Oral
 LD50
 Rat
 5800 mg/kg

Material name: SCRUBS® Graffiti & Spray Paint Remover Towels

Components Species Test Results

Dimethyl Glutarate (CAS 1119-40-0)

Acute Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Oral

LD50 Rat > 2000 mg/kg

Dimethyl succinate (CAS 106-65-0)

Acute Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Oral

LD50 Rat 6900 mg/kg

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

Acute Dermal

LD50 Rabbit 400 mg/kg

Oral

LD50 Rat 530 - 2800 mg/kg

Propylene Glycol Methyl Ether (CAS 107-98-2)

Acute Dermal

LD50 Rat > 2000 mg/kg, Days

Inhalation

LC50 Rat 55 mg/l, 4 Hours

Oral

LD50 Rat > 2000 mg/kg

Tripropylene Glycol methyl ether (CAS 25498-49-1)

Acute Dermal

LD50 Rabbit 15000 mg/kg, 24 Hours

Prolonged skin contact may cause temporary irritation.

Oral

LD50 Rat 3400 mg/kg

Skin corrosion/irritation Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

Acetone (CAS 67-64-1)

A4 Not classifiable as a human carcinogen.

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

A3 Confirmed animal carcinogen with unknown relevance to

numans.

Propylene Glycol Methyl Ether (CAS 107-98-2)

A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

	Species	Test Results
EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
utyl Ether (CAS 11	1-76-2)	
LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
CAS 628-63-7)		
LC50	Western mosquitofish (Gambusia affinis)) 65 mg/l, 96 hours
S 1310-73-2)		
EC50	Water flea (Ceriodaphnia dubia)	34.59 - 47.13 mg/l, 48 hours
LC50	Western mosquitofish (Gambusia affinis)) 125 mg/l, 96 hours
	EC50 LC50 utyl Ether (CAS 11 LC50 CAS 628-63-7) LC50 S 1310-73-2) EC50	EC50 Water flea (Daphnia magna) LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) utyl Ether (CAS 111-76-2) LC50 Inland silverside (Menidia beryllina) CAS 628-63-7) LC50 Western mosquitofish (Gambusia affinis) S 1310-73-2) EC50 Water flea (Ceriodaphnia dubia)

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

-0.24Acetone Dimethyl succinate 0.35 Ethylene Glycol Monobutyl Ether 0.83 Primary Amyl Acetate 2.3

Mobility in soil Not established.

The product contains volatile organic compounds which have a photochemical ozone creation Other adverse effects

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code

Dispose in accordance with all applicable regulations. D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1263

UN proper shipping name Paint related material including paint thinning, drying, removing, or reducing compound

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group ||

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 149, B52, IB2, T4, TP1, TP8, TP28

Packaging exceptions 150
Packaging non bulk 173
Packaging bulk 242

IATA

UN number UN1263

UN proper shipping name Paint related material (including paint thinning or reducing compounds)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Allowed with restrictions.

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1263

UN proper shipping name PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid

lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards

Marine pollutant No. EmS F-E, <u>S</u>-<u>E</u>

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

DOT





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Primary Amyl Acetate (CAS 628-63-7)

Sodium Hydroxide (CAS 1310-73-2)

Listed.

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Yes

categories Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and

Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

Primary Amyl Acetate (CAS 628-63-7)

Propylene Glycol Methyl Ether (CAS 107-98-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Propylene Glycol Methyl Ether (CAS 107-98-2) Sodium Hydroxide (CAS 1310-73-2)

Inventory name

International Inventories

Australia

Country(s) or region

Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Australian Inventory of Chemical Substances (AICS)

16. Other information, including date of preparation or last revision

 Issue date
 12-04-2018

 Revision date
 01-15-2020

Version # 02

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Revision information Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties

Transport Information: Proper Shipping Name/Packing Group

GHS: Classification

On inventory (yes/no)*

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).