KELLY-MOORE* PAINTS The Painter's Paint Store

SAFETY DATA SHEET

1. Identification

Product identifier 147 KM Commercial Exterior Acrylic Satin Series (122, 333, 555)

Other means of identification None

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Kelly-Moore Paint Co., Inc.

Address 987 Commercial St., San Carlos, CA 94070

Telephone 1-800-874-4436

E-mail TAlvarez@kellymoore.com

Contact person Tiffany Alvarez

Emergency phone number CHEMTREC: 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental informationThis product contains Diphenyl Ketone at less than 0.2% which is suspected of causing cancer

(See Section 11).

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|--|------------|-------|
| Titanium dioxide | 13463-67-7 | 10-20 |
| Propane -1,2 -diol | 57-55-6 | <10 |
| Silicon dioxide, crystalline silica-free | 7631-86-9 | 1-5 |
| Diphenyl ketone | 119-61-9 | <0.2 |

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

147 KM Commercial Exterior Acrylic Satin Series (122, 333, 555) 930004 Version #: 01 Revision date: - Issue date: 28-August-2015

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Get medical attention if any discomfort

continues.

Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of Skin contact

water. Get medical attention if irritation persists after washing.

Any material that contacts the eye should be washed out immediately with water. If easy to do, Eye contact

remove contact lenses. Get medical attention if symptoms persist.

Ingestion Immediately rinse mouth and drink plenty of water. Keep person under observation. If person

Direct contact with eyes may cause temporary irritation.

becomes uncomfortable take to hospital along with these instructions.

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

General information If exposed or concerned: get medical attention/advice.

Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters During fire, gases hazardous to health may be formed.

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed

containers cool.

Fire fighting equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Avoid inhalation of vapors and contact with skin and eyes. Wear appropriate personal protective equipment (See Section 8).

Methods and materials for containment and cleaning up Should not be released into the environment. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Large Spills: Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. This product is moderately soluble in water.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapor, Avoid contact with eyes, skin, and clothing, Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store away from incompatible materials (see Section 10 of the SDS). Store in tightly closed original container in a dry, cool and well-ventilated place.

147 KM Commercial Exterior Acrylic Satin Series (122, 333, 555) 930004 Version #: 01 Revision date: - Issue date: 28-August-2015

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Туре | Value | Form | |
|-----------------------------------|------|-----------|----------|--|
| Diphenyl ketone (CAS 119-61-9) | TWA | 0.5 mg/m3 | | |
| Propane -1,2 -diol (CAS 57-55-6) | TWA | 10 mg/m3 | Aerosol. | |

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Use safety glasses, goggles, or face shield to protect eyes.

Skin protection

Hand protection Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent

change is advisable.

Wear suitable protective clothing. Other

Respiratory protection Use NIOSH certified, air purifying respirators with N-, P-, or R- series particulate filter and organic

> vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. protection provided by air-purifying respirators is limited. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134. Consult a qualified industrial hygienist or Safety Professional for respirator selection

guidance.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Milky white to colored liquid.

Liquid. Physical state Liquid. **Form** Various. Color

Slightly ammoniacal. Odor

Not available. Odor threshold

7 - 10

Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point Not available. **Evaporation rate** < 1 (n-BuAc=1) Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Not available. Vapor pressure Vapor density >= 1 (Air=1) Relative density Not available. Solubility(ies)

Solubility (water) Moderately soluble

Partition coefficient

Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Not available. **Viscosity**

Other information

VOC (Weight %) 43.7 - 46.58 g/L

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Contact with incompatible materials. Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged or repeated contact may dry skin and cause irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Not available. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Exposure may cause temporary irritation, redness, or discomfort.

Information on toxicological effects

Acute toxicity Ingestion may cause irritation and malaise. In high concentrations, vapors and spray mists are

narcotic and may cause headache, fatigue, dizziness and nausea.

Prolonged or repeated contact may dry skin and cause irritation. Skin corrosion/irritation

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity The product contains a small amount substance that is suspected of causing cancer. Inhalation of

titanium dioxide dust may cause cancer, however due to the physical form of the product,

inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Diphenyl ketone (CAS 119-61-9) 2B Possibly carcinogenic to humans.

Silicon dioxide, crystalline silica-free (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged or repeated contact may dry skin and cause dermatitis.

Further information Components of the product may be absorbed into the body through the skin.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | | Species | Test Results |
|----------------------|-----------|--------------------------------------|----------------------------|
| Diphenyl ketone (CAS | 119-61-9) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 0.21 - 0.37 mg/l, 24 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 13.2 - 15.3 mg/l, 96 hours |
| | | | 5.96 - 7.41 mg/l, 7 days |

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Propane -1,2 -diol (CAS 57-55-6) -0.92

Mobility in soil The product is water soluble and may spread in water systems.

Other adverse effects None known.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose in accordance with applicable federal, state, and local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

דחח

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Diphenyl ketone (CAS 119-61-9) 0.1 % One-Time Export Notification only.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

147 KM Commercial Exterior Acrylic Satin Series (122, 333, 555)
930004 Version #: 01 Revision date: - Issue date: 28-August-2015

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Propane -1,2 -diol (CAS 57-55-6)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Propane -1,2 -diol (CAS 57-55-6)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Toxic Substances Control Act (TSCA) Inventory

Diphenyl ketone (CAS 119-61-9)

International Inventories

Country(s) or region Inventory name

On inventory (yes/no)*

Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 28-August-2015

Revision date - Version # 01

United States & Puerto Rico

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 1*

Flammability: 1 Physical hazard: 0

930004 Version #: 01 Revision date: - Issue date: 28-August-2015

References ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

EPA: AQUIRE database

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Kelly-Moore Paint Co., Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.