# **SAFETY DATA SHEET**

63025/71033

## Section 1. Identification

Product name	: MINWAX® Water Based Oil-Modified Polyurethane Clear Satin
Product code	: 63025/71033
Other means of identification	: Not available.
CAS #	: Not applicable.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Not applicable.	
Manufacturer	: MINWAX Company 10 Mountainview Road Upper Saddle River, NJ 07458
Emergency telephone number of the company	: (216) 566-2917
Product Information Telephone Number	: (800) 523-9299
Regulatory Information Telephone Number	: (216) 566-2902
Transportation Emergency Telephone Number	: (800) 424-9300

# Section 2. Hazards identification

OSHA/HCS status	<ul> <li>This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).</li> </ul>
Classification of the substance or mixture	: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION (Unborn child) - Category 1B
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: Causes serious eye irritation. Causes skin irritation. May damage the unborn child.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling.

Date of issue/Date of revision	: 12/23/2016	Date of previous issue	: 7/15/2016	Version : 4	1/12
--------------------------------	--------------	------------------------	-------------	-------------	------

## Section 2. Hazards identification

: IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
: Store locked up.
<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

#### CAS number/other identifiers

Ingredient name	% by weight	CAS number
1-Methyl-2-Pyrrolidone 2-Methoxymethylethoxypropanol	5.5 1.86	872-50-4 34590-94-8
Dimethylethanol Amine	1.35	108-01-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessary first aid measures		
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>	
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.	

Date of issue/Date of revision	: 12/23/2016	Date of previous issue	: 7/15/2016	Version : 4	2/12

# Section 4. First aid measures

Ingestion	<ul> <li>Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and</li> </ul>
	the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/ Potential acute health effe	
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	-
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

-	
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling				
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.		
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.		
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.		

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

posure limits
HA WEEL (United States, 10/2011). sorbed through skin.
WA: 10 ppm 8 hours. <b>CGIH TLV (United States, 3/2016).</b> <b>sorbed through skin.</b> WA: 100 ppm 8 hours. WA: 606 mg/m <sup>3</sup> 8 hours. TEL: 150 ppm 15 minutes. TEL: 909 mg/m <sup>3</sup> 15 minutes. <b>DSH REL (United States, 10/2013).</b>
sorbed through skin. WA: 100 ppm 10 hours. WA: 600 mg/m <sup>3</sup> 10 hours. TEL: 150 ppm 15 minutes. TEL: 900 mg/m <sup>3</sup> 15 minutes. SHA PEL (United States, 6/2016).
<b>sorbed through skin.</b> WA: 100 ppm 8 hours. WA: 600 mg/m³ 8 hours. ne.
)

**Occupational exposure limits (Canada)** 

### Section 8. Exposure controls/personal protection

1-Methyl-2-Pyrrolidone CA Or Dimethylethanol Amine CA Or STEL TWA	Section 8. Exposure controls/personal protection				
Dimethylethanol AmineTWA CA O STEI TWA STEI TWAAppropriate engineering controls:If user operations generate dust, fumes, gas, v local exhaust ventilation or other engineering of airborne contaminants below any recommended Environmental exposure 	osure limits				
controlslocal exhaust ventilation or other engineering of airborne contaminants below any recommendedEnvironmental exposure controlsEmissions from ventilation or work process equ they comply with the requirements of environm cases, fume scrubbers, filters or engineering n will be necessary to reduce emissions to acceptIndividual protection measures*Hygiene measures*Hygiene measures*Wash hands, forearms and face thoroughly aft eating, smoking and using the lavatory and at 1 Appropriate techniques should be used to rem Wash contaminated clothing before reusing. E showers are close to the workstation location.Eye/face protection*Safety eyewear complying with an approved st assessment indicates this is necessary to avoi gases or dusts. If contact is possible, the folio the assessment indicates a higher degree of p worn at all times when handling chemical prod necessary. Considering the parameters specif during use that the gloves are still retaining the noted that the time to breakthrough for any glo glove manufacturers. In the case of mixtures, protection time of the gloves cannot be accura performed and the risks involved and should b handling this product.Other skin protection*Appropriate footwear and any additional skin p based on the task being performed and the risk	Ontario Provincial (Canada, 7/2015). A: 400 mg/m <sup>3</sup> 8 hours. Ontario Provincial (Canada, 7/2015). EL: 22 mg/m <sup>3</sup> 15 minutes. A: 11 mg/m <sup>3</sup> 8 hours. EL: 6 ppm 15 minutes. A: 3 ppm 8 hours.				
controlsLinkey comply with the requirements of environm cases, fume scrubbers, filters or engineering n will be necessary to reduce emissions to acceptIndividual protection measuresWash hands, forearms and face thoroughly aft eating, smoking and using the lavatory and at th Appropriate techniques should be used to rem Wash contaminated clothing before reusing. E showers are close to the workstation location.Eye/face protectionSafety eyewear complying with an approved st assessment indicates this is necessary to avoi gases or dusts. If contact is possible, the follor the assessment indicates a higher degree of pSkin protectionChemical-resistant, impervious gloves complyi worn at all times when handling chemical prod necessary. Considering the parameters specifi during use that the gloves are still retaining the noted that the time to breakthrough for any glo glove manufacturers. In the case of mixtures, protection time of the gloves cannot be accurated performed and the risks involved and should be handling this product.Other skin protectionAppropriate footwear and any additional skin p based on the task being performed and the risk	controls to keep worker exposure to				
Hygiene measures: Wash hands, forearms and face thoroughly aft eating, smoking and using the lavatory and at t Appropriate techniques should be used to rem Wash contaminated clothing before reusing. E showers are close to the workstation location.Eye/face protection: Safety eyewear complying with an approved st assessment indicates this is necessary to avoi gases or dusts. If contact is possible, the follor the assessment indicates a higher degree of pSkin protection:Hand protection:Body protection:Body protection:Personal protective equipment for the body sho performed and the risks involved and should b handling this product.Other skin protection:Appropriate footwear and any additional skin p based on the task being performed and the risk	nental protection legislation. In some modifications to the process equipment				
<ul> <li>eating, smoking and using the lavatory and at a Appropriate techniques should be used to remewing the contaminated clothing before reusing. E showers are close to the workstation location.</li> <li>Eye/face protection         <ul> <li>Safety eyewear complying with an approved st assessment indicates this is necessary to avoin gases or dusts. If contact is possible, the follow the assessment indicates a higher degree of p</li> </ul> </li> <li>Skin protection         <ul> <li>Chemical-resistant, impervious gloves complying worn at all times when handling chemical produnceessary. Considering the parameters specified uring use that the gloves are still retaining the noted that the time to breakthrough for any glo glove manufacturers. In the case of mixtures, protection time of the gloves cannot be accurated and the risks involved and should be handling this product.</li> <li>Other skin protection</li> <li>Appropriate footwear and any additional skin p based on the task being performed and the risks</li> </ul> </li> </ul>					
Skin protectionHand protectionHand protectionBody protectionBody protectionCother skin protection <td>the end of the working period. hove potentially contaminated clothing. Ensure that eyewash stations and safety</td>	the end of the working period. hove potentially contaminated clothing. Ensure that eyewash stations and safety				
<ul> <li>Hand protection</li> <li>Chemical-resistant, impervious gloves complyi worn at all times when handling chemical product necessary. Considering the parameters specified uring use that the gloves are still retaining the noted that the time to breakthrough for any glog glove manufacturers. In the case of mixtures, protection time of the gloves cannot be accurated and the risks involved and should be handling this product.</li> <li>Other skin protection</li> <li>Chemical-resistant, impervious gloves complying the parameters specified uring use that the gloves are still retaining the noted that the time to breakthrough for any glog glove manufacturers. In the case of mixtures, protection time of the gloves cannot be accurated and the risks involved and should be handling this product.</li> </ul>	oid exposure to liquid splashes, mists, powing protection should be worn, unless				
worn at all times when handling chemical product necessary. Considering the parameters specified uring use that the gloves are still retaining the noted that the time to breakthrough for any glo glove manufacturers. In the case of mixtures, protection time of the gloves cannot be accuratedBody protectionPersonal protective equipment for the body show performed and the risks involved and should be 					
Other skin protectionperformed and the risks involved and should be handling this product.Other skin protection: Appropriate footwear and any additional skin p based on the task being performed and the risk	ducts if a risk assessment indicates this is ified by the glove manufacturer, check eir protective properties. It should be ove material may be different for different , consisting of several substances, the				
based on the task being performed and the ris					
Respiratory protection       : Based on the hazard and potential for exposure appropriate standard or certification. Respirator respiratory protection program to ensure proper aspects of use.	tors must be used according to a				

# Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 8

Date of issue/Date of revision

: 12/23/2016

Date of previous issue

: 7/15/2016

### Section 9. Physical and chemical properties

: Not available.
: 100°C (212°F)
: Closed cup: >93.3°C (>199.9°F)
: 0.8 (butyl acetate = 1)
: Not available.
: Lower: 1.1% Upper: 14%
: 0.31 kPa (2.333 mm Hg) [at 20°C]
: 1 [Air = 1]
: 1.05
: Not available.
: Kinematic (40°C (104°F)): >0.205 cm <sup>2</sup> /s (>20.5 cSt)
: Not applicable.
: 2.971 kJ/g

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
1-Methyl-2-Pyrrolidone	LD50 Dermal	Rabbit	8 g/kg	-
	LD50 Oral	Rat	3914 mg/kg	-
Dimethylethanol Amine	LC50 Inhalation Gas.	Rat	1641 ppm	4 hours
5	LD50 Oral	Rat	2 g/kg	-

Date of issue/Date of revision

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-Methyl-2-Pyrrolidone	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
2-Methoxymethylethoxypropanol	Eyes - Mild irritant Eyes - Mild irritant	Human Rabbit	-	8 milligrams 24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
Dimethylethanol Amine	Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit	-	5 microliters 445 milligrams	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### <u>Specific target organ toxicity (repeated exposure)</u> Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>ets</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact Ingestion	<ul> <li>Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations</li> <li>Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations</li> </ul>
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	f <u>fects</u>
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: May damage the unborn child.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	48024.4 mg/kg
Inhalation (gases)	121286 ppm

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
1-Methyl-2-Pyrrolidone	Acute LC50 1.23 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 832 ppm Fresh water	Fish - Lepomis macrochirus	96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil

Date of issue/Date of revision

### Section 12. Ecological information

Soil/water p	oarti	tion
coefficient	(Koc)	)

: Not available.

Other adverse effects

ects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precaution Transport in bulk a to Annex II of MAR	consid mode suitab prior ta respon unload substa	ler container sizes. T of transport (sea, ain ly for that mode of tr o shipment, and com nsibility of the persor ding dangerous good ances and on all acti	The presence of a s r, etc.), does not ind ansport. All packagi ppliance with the ap n offering the product as must be trained c	hipping description licate that the produ- ing must be review plicable regulations of for transport. Peo on all of the risks de	uct is packaged ed for suitability is the sole ople loading and
the IBC Code	Proper	shipping name	: Not available.		
	Ship ty	pe	: Not available.		

### Section 15. Regulatory information

#### SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

#### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Section 16. Other information

#### Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Procedure used to derive the classification

	ION - Category 2 ′E IRRITATION - Category 2A I (Unborn child) - Category 1B	Justification Calculation method Calculation method Calculation method		
<u>History</u>				
Date of printing	: 12/23/2016			
Date of issue/Date of revision	: 12/23/2016			
Date of previous issue	: 7/15/2016			
Version	: 4			
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations			

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use

Date of issue/Date of revision : 12/23/20	6 Date of previous issue	: 7/15/2016	Version : 4	11/12
---	--------------------------	-------------	-------------	-------

### Section 16. Other information

of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.