

Safety Data Sheet

Freeman Green Styro Glue

Date of Preparation : November 1, 2013

Section 1 Chemical Product and Company Identification

Product/Chemical Name: Freeman Green Styro Glue

Chemical Family: Solvent

CAS Number: N/A

Other Designations: N/A

General Use: N/A

Manufacturer: Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011

Phone (440) 934-1902, FAX (440) 934-7200, Hours of Operation 8-5,

Emergency phone number 1-800-424-9300

HMIS	
H	3
F	3
R	0
PPE Sec.8.	

Section 2 Composition/Information on Ingredients

Ingredient Name	CAS Number
Methyl Alcohol	67-56-1

Ingredient	OSHA PEL		ACGIH TLV		Vapor Pressure
	TWA	STEL	TWA	STEL	
Methyl Alcohol	200ppm Skin	250 ppm Skin	200 ppm Skin	250 ppm Skin	98 mm Hg @ 68°F

Section 3 Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Flammable. Ingestion. Skin Irritation

Potential Health Effects

Primary Entry Routes: Eye contact, skin contact, inhalation, ingestion, skin absorption.

Acute Effects:

Inhalation: Breathing large amounts may be harmful. Toxic effects exerted upon nervous system, particularly the optic nerve. Symptoms include headache, drowsiness, nausea, visual impairment (including blindness), coma and death.

Eye: Irritant

Skin: Frequent or prolonged contact may irritate and cause dermatitis. May be absorbed through the skin, and symptoms parallel inhalation

Ingestion: Toxic. Symptoms parallel inhalation. Can intoxicate and cause blindness

Target Organ Effects: Exposure to lethal concentrations of methanol has been shown to cause damage to organs including liver, kidneys, pancreas, heart, lungs and brain.

Chronic Effects: Marked impairment of vision, skin irritation

Freeman Green Styro Glue

Section 4 First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen and/or artificial respiration.

Eye Contact: Check for and remove contact lenses. Flush with plenty of water for 15 minutes and get medical attention.

Skin Contact: Wash thoroughly with soap and water. Remove contaminated clothing and laundry before reuse. Destroy contaminated shoes.

Ingestion: Do induce vomiting, as directed by medical personnel. . If individual is drowsy or unconscious, do not give anything by mouth; Get medical attention immediately

Section 5 Fire Fighting Measures

Flash Point: 52 °F (11 °C)

Flash Point Method: TCC


LEL: 6 % v/v

UEL: 36 % v/v

Extinguishing Media: Alcohol Foam, , CO₂, or dry chemical (water may be ineffective)

Fire-Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Decomposition and combustion products may be toxic.



Section 6 Accidental Release Measures

Spill /Leak Procedures: Stop spill at source .Eliminate all sources of ignition, such as smoking, sparks or flames. Dike area and contain. Clean up remainder with absorbent materials such as sand or vermiculite. Mop up and dispose of.

Section 7 Handling and Storage

Handling & Storage: Use with adequate ventilation. Avoid prolonged breathing of vapor. Avoid prolonged or repeated contact with skin. Wear safety goggles or face shield. Wear gloves, apron and footwear impervious to this material. Wash clothing before reuse. Store at ambient temperatures. Keep container tightly closed and upright when not in use to prevent leakage.

Section 8 Exposure Controls/Personal Protection

Ventilation: Local exhaust recommended. General mechanical is acceptable. Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2).

Respiratory Protection: Use a NIOSH approved respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Skin Protection: Wear impermeable gloves.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Freeman Green Styro Glue

Section 9 Physical and Chemical Properties

Appearance and Odor: Green liquid/ Mild alcohol odor

Vapor Pressure: 96 mm Hg at 68 °F (20 °C)

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1, at 4 °C): 0.9

Water Solubility: 50-75% by volume, est.

Boiling Point: 148°F (63.8°C) at 760 mmHg

% Volatile: N/A

Evaporation Rate (N-Butyl Acetate = 1) : >1

VOC: 4.76 lb/gal

Section 10 Stability and Reactivity

Stability: Stable.

Polymerization: Hazardous polymerization will not occur.

Chemical Incompatibilities: Strong oxidizing agents

Conditions to Avoid: Heat, sparks and flame

Hazardous Decomposition Products: Carbon dioxide and carbon monoxide.

Section 11 Toxicological Information

Acute Inhalation Exposure Effects: Respiratory irritant.

Skin Irritation: Irritant.

Eye Irritation: Irritant, will injure eye tissue.

Section 12 Ecological Information

Expected to be slightly toxic to aquatic organisms

Section 13 Disposal Considerations

Disposal: Use safety containers for disposal. Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations

Empty Container Warning: "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Section 14 Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name Paint

Shipping Symbols:

Hazard Class: 3

ID No.: UN 1263

Packing Group: II

Label: Flammable Liquid

Special Provisions (172.102):

Freeman Green Styro Glue

Section 15 Regulatory Information

US Federal Regulations:

OSHA (Occupational Safety and Health Act): This Material Safety Data Sheet has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

CERCLA:

If the reportable quantity of this product is accidentally spilled, the incident is subject to the provisions of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) and must be reported to the National Response Center by calling 800-424-8802.

The reportable spill quantity of this product is 7000 pounds.

This product contains: Methanol.

RCRA (Resource Conservation and Recovery Act): Not a hazardous waste under RCRA (40 CFR 261).

SARA 311/312 Codes: Fire. Immediate Health. Chronic

SARA Toxic Chemical (40 CFR 372.65): This product contains the following toxic chemical subject to the reporting requirements of Section 313 of SARA Title III of 1986 and of 40 CFR 372

This product contains the following Section 313 Reportable ingredients:

<u>COMPONENT</u>	<u>CAS No.</u>	<u>MAXIMUM %</u>
Methyl Alcohol	67-56-1	70%

TSCA Inventory Status: All ingredients listed on TSCA inventory requirements.

State Regulations: California Proposition 65 - None

Listed on the following states Right to Know Lists: Methanol (CAS # 67-56-1) is listed on the New Jersey and Pennsylvania Right to Know Lists

Section 16 Other Information

Disclaimer: The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.