MATERIAL SAFETY DATA SHEET

W.H.M.I.S. CLASSIFICATION: NON-CONTOLLED

PRODUCT NAME: Roberts 8015 Solvent Free Universal Carpet Seam Sealer

Roberts MSDS Code #8015C

PRODUCT USES: Applied to cut edges during carpet installations

V.O.C. CONTENT: 0 Calculated

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ROBERTS COMPANY CANADA LTD.

ADDRESS: 2070 Steeles Ave. Bramalea, Ontario L6T 1A7

24 HOUR (CANUTEC) PHONE: (613) 996-6666

December 01/06

NAME OF PREPARER: Technical Dept.

INFORMATION PHONE: (905) 791-4444

SOURCES USED: Raw material supplier M.S.D.S.

SECTION II - HAZARDOUS INGREDIENTS INFORMATION

COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50		
NO REPORTABLE INGREDIENTS							

SECTION III - PHYSICAL DATA

BOILING POINT: 100° C FREEZING POINT: Approx. 0°C SPECIFIC GRAVITY (H20=1): 1.04 pH: Approx. 5

 VAPOUR DENSITY (AIR=1):
 >1

 VAPOUR PRESSURE (MM OF MERCURY):
 N/A

 EVAPORATION RATE (BUTYL ACETATE=1): As for water

 EVAPORATION RATE (ETHYL ACETATE=1): As for water

SOLUBILITY IN WATER: Dilatable emulsion PERCENT VOLATILE: 50

APPEARANCE AND ODOUR: White liquid, mild odour. ODOUR THRESHOLD (PPM): Not available

SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT (specify method): None METHOD USED: IMPACT SENSITIVITY: Insensitive

FLAMMABLE LIMITS (% BY VOLUME): LOWER: N/A UPPER: N/A SENSITIVITY TO STATIC DISCHARGE: Insensitive

FIRE EXTINGUISHING MEDIA: Water Spray, Foam, CO2, Dry Chemical AUTO IGNITION TEMP: N/A TDG FLAMMABILITY CLASSIFICATION: Not regulated.

SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION V - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: Excessive Heat, Freezing

INCOMPATIBILITY (Materials to avoid): None

HAZARDOUS DECOMPOSITION PRODUCTS: May be generated if product engulfed in fire.

HAZARDOUS POLYMERIZATION: Will not occur CONDITIONS TO AVOID: None

SECTION VI – TOXICOLOGICAL PROPERTIES ENTRY ROUTE TABLE

SKIN CONTACT X SKIN ABSORPTION EYE CONTACT X INHALATION ACUTE X INHALATION CHRONIC INGESTION X

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Eye contact may cause irritation. Ingestion may cause vomiting. Gastrointestinal upset. Inhalation may cause headache, nausea, and irritation of nose and throat

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Prolonged skin contact may cause irritation. Kidney disorders may be aggravated by exposure.

LD50 (SPECIFY SPECIES & ROUTE):	LC50 (SPECIFY SPECIES):	EXPOSURE LIMIT:	IRRITANCY:
Not available	Not available	Not available	May irritate eyes and skin
SENSITIZING CAPACITY:	CARCINOGENICITY:	REPRODUCTIVITY EFFECTS:	SYNERGISTIC MATERIALS:
None known	None	None known	None known

SECTION VII - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): Not required under normal conditions of use.

VENTILATION: General dilution ventilation.

PROTECTIVE GLOVES: Polyethylene, PVC, natural rubber EYE PROTECTION: Goggles

OTHER PROTECTIVE EQUIPMENT: None required.

SPILL PROCEDURES: Absorb or scrape up. Wash area with water to remove residue. Spilled material may cause slippery conditions. Promptly report significant spills to appropriate authorities.

Consult local regulations.

WASTE DISPOSAL METHOD: Destroy by incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.

STORAGE & HANDLING PRECAUTIONS: Store and employ in ventilated area, as close to room temperature as possible.

OTHER PRECAUTIONS: Keep containers closed when not in use. Keep out of reach of children.

SECTION VIII - FIRST AID MEASURES

INHALATION: Remove to fresh air. Restore breathing if necessary. Obtain medical attention immediately. EYES: Flush with water for 20 minutes holding eyelids open. Obtain medical attention immediately.

SKIN: Wash affected area with soap and water. Remove contaminated clothing and launder before re-use. Consult physician if irritation develops. **INGESTION:** Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Contact physician immediately.