

## 1. Product and Company Identification

<b>Product identifier</b>	<b>Degreasing Solvent EF (4083-75)</b>
<b>Other means of identification</b>	Not available
<b>Recommended use</b>	Degreaser
<b>Recommended restrictions</b>	None known.
<b>Manufacturer</b>	Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)

## 2. Hazards Identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement**  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause drowsiness or dizziness.  
 Suspected of damaging the unborn child.  
 May cause damage to organs through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways.

**Precautionary statement**

**Prevention**  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.  
 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.  
 Do not breathe gas. Use only outdoors or in a well-ventilated area.

**Response**  
 If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.  
 Specific treatment (see this label). If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
 If exposed or concerned: Get medical advice/attention.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.  
 If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

**Storage**  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal**  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	Not applicable.

### 3. Composition/Information on Ingredients

#### Mixture

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	49-51
Heptane		142-82-5	43-45
Heptane, Branched, Cyclic And Linear		426260-76-6	43-45
Carbon dioxide		124-38-9	4-6
Toluene		108-88-3	1-3

### 4. First Aid Measures

<b>Inhalation</b>	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
<b>Skin contact</b>	If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
<b>Eye contact</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	If swallowed: Immediately call a poison center/doctor. DO NOT induce vomiting.
<b>Most important symptoms/effects, acute and delayed</b>	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause drowsiness or dizziness. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wear suitable protective clothing.

### 5. Fire Fighting Measures

<b>Suitable extinguishing media</b>	Powder. Alcohol resistant foam. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	Not available.
<b>Sensitivity to static discharge</b>	Not available.

### 6. Accidental Release Measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

**Methods and materials for containment and cleaning up**

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Dike far ahead of spill for later disposal. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

---

## 7. Handling and Storage

---

**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe gas. Avoid contact during pregnancy/while nursing. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use personal protective equipment as required. Wash hands thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Contents under pressure. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid exposure to long periods of sunlight. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

---

## 8. Exposure Controls/Personal Protection

---

**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3
		1000 ppm
Carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm
Heptane (CAS 142-82-5)	PEL	2000 mg/m3
		500 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
		30000 ppm
	TWA	9000 mg/m3
		5000 ppm
Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3
		440 ppm
	TWA	350 mg/m3
		85 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection**

Wear protective gloves.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

Wear positive pressure self-contained breathing apparatus (SCBA). In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards**

Not applicable.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and Chemical Properties**

<b>Appearance</b>	Clear
<b>Physical state</b>	Gas.
<b>Form</b>	Aerosol
<b>Color</b>	Colorless
<b>Odor</b>	Solvent
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not applicable
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	0.728 (Concentrate)
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.

**Upper/lower flammability or explosive limits**

<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	55 - 65 psig @ 70°F
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Partial
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	< 20.5 m <sup>2</sup> /s
<b>Other information</b>	
<b>Flame extension</b>	> 100 cm
<b>Flammability (flash back)</b>	Yes
<b>Heat of combustion</b>	45.2 kJ/g
<b>VOC (Weight %)</b>	44.7 %

---

**10. Stability and Reactivity**

---

<b>Reactivity</b>	Do not mix with other chemicals.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Acids.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

---

**11. Toxicological Information**

---

<b>Routes of exposure</b>	Inhalation. Ingestion. Skin contact. Eye contact.
<b>Information on likely routes of exposure</b>	
<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Inhalation</b>	Prolonged inhalation may be harmful. May cause damage to organs by inhalation. Narcotic effects.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Information on toxicological effects**

**Acute toxicity** Narcotic effects.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	15800 mg/kg 20 ml/kg
<i>Inhalation</i>		
LC50	Mouse	44000 mg/m <sup>3</sup> /4H
	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours 39 mg/l/4h

Components	Species	Test Results
<i>Oral</i> LD50	Human	2857 mg/kg
	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Carbon dioxide (CAS 124-38-9)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Not available	
Heptane (CAS 142-82-5)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	103 mg/l, 4 Hours
LD50	Mouse	75 mg/l, 2 Hours
<i>Oral</i>		
LD50	Rat	15000 mg/kg
Heptane, Branched, Cyclic And Linear (CAS 426260-76-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Not available	
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	12196 mg/kg, Sigma 12125 mg/kg 8390 mg/kg 14.1 ml/kg
<i>Inhalation</i>		
LC50	Mouse	7100 mg/l, 4 Hours 5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours <= 28800 mg/m <sup>3</sup> , 4 Hours, Sigma 12200 ppm, 2 Hours 8000 ppm, 4 Hours 12.5 mg/l/4h
<i>Oral</i>		
LD50	Rat	> 5580 mg/kg, Sigma 636 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	

<b>Conjunctival reddening value</b>	Not available.
<b>Conjunctival oedema value</b>	Not available.
<b>Recover days</b>	Not available.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, NTP, or OSHA.
<b>ACGIH Carcinogens</b>	
Acetone (CAS 67-64-1)	A4 Not classifiable as a human carcinogen.
Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Toluene (CAS 108-88-3)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.
<b>US - California Proposition 65 - CRT: Listed date/Carcinogenic substance</b>	
Benzene (CAS 71-43-2)	Carcinogenic.
Benzene, ethyl- (CAS 100-41-4)	Carcinogenic.
<b>Reproductive toxicity</b>	Suspected of damaging the unborn child.
<b>Teratogenicity</b>	Toluene (benzene, methyl-) has caused fetotoxicity (reduced fetal weight), behavioural effects (effects on learning and memory) and hearing loss (in males). These effects have been observed in the offspring of rats exposed by inhalation to 1200 or 1800 ppm toluene. These effects were observed in the absence of maternal toxicity.
<b>Specific target organ toxicity - single exposure</b>	Narcotic effects.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.
<b>Further information</b>	Not available.
<b>Name of Toxicologically Synergistic Products</b>	Not available.

---

## 12. Ecological Information

---

<b>Ecotoxicity</b>	See below		
<b>Components</b>		<b>Species</b>	<b>Test Results</b>
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Heptane (CAS 142-82-5)			
<b>Aquatic</b>			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Algae	IC50	Algae	433 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of this product.		

<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	No data available.
<b>Mobility in general</b>	Not available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

### 13. Disposal Considerations

---

<b>Disposal instructions</b>	Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>US RCRA Hazardous Waste U List: Reference</b>	
Acetone (CAS 67-64-1)	U002
Toluene (CAS 108-88-3)	U220
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

---

### 14. Transport Information

---

#### U.S. Department of Transportation (DOT)

##### Basic shipping requirements:

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable
<b>Hazard class</b>	Limited Quantity - US
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306

#### Transportation of Dangerous Goods (TDG - Canada)

##### Basic shipping requirements:

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	AEROSOLS, flammable
<b>Hazard class</b>	Limited Quantity - Canada
<b>Special provisions</b>	80

#### IATA/ICAO (Air)

##### Basic shipping requirements:


<b>UN number</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable
<b>Hazard class</b>	Limited Quantity - IATA

#### IMDG (Marine Transport)

##### Basic shipping requirements:

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	AEROSOLS, flammable
<b>Hazard class</b>	Limited Quantity - US

#### DOT; IMDG; TDG







## 15. Regulatory Information

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

**Canada CEPA Schedule I: Listed substance**

Carbon dioxide (CAS 124-38-9) Listed.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Heptane (CAS 142-82-5) 1 TONNES

Toluene (CAS 108-88-3) 1 TONNES

**Canada WHMIS Ingredient Disclosure: Threshold limits**

Acetone (CAS 67-64-1) 1 %

Carbon dioxide (CAS 124-38-9) 1 %

Heptane (CAS 142-82-5) 1 %

Toluene (CAS 108-88-3) 1 %

**WHMIS status** Controlled

**WHMIS classification** Class A - Compressed Gas, Class B - Division 5 - Flammable Aerosol, Class D - Division 2A, 2B

**WHMIS labeling**



**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration**

Toluene (CAS 108-88-3) 1.0 %

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Toluene (CAS 108-88-3) Listed.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**US CWA Section 311 Hazardous Substances: Listed substance**

Toluene (CAS 108-88-3) Listed.

**US CWA Section 307(a)(1) Toxic Pollutants: Listed substance**

Toluene (CAS 108-88-3) Listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetone (CAS 67-64-1) Listed.

Heptane (CAS 142-82-5) Listed.

Toluene (CAS 108-88-3) Listed.

**US – CAA Mandatory Reporting of GHGs: Global warming potential (100 year)**

Carbon dioxide (CAS 124-38-9) 1

**US CAA Section 111 Volatile Organic Compounds: Listed substance**

Acetone (CAS 67-64-1) Listed.

Toluene (CAS 108-88-3) Listed.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3) Listed.

**US CAA Section 612 SNAP Program: Listed substance**

Acetone (CAS 67-64-1) Listed.

Carbon dioxide (CAS 124-38-9) Listed.

**US CAA VOCs with Negligible Photochemical Activity: Listed substance**

Acetone (CAS 67-64-1) Listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Toluene	108-88-3	1-3

**Other federal regulations**

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**US state regulations**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Hazardous Substances (Director's): Listed substance**

Acetone (CAS 67-64-1) Listed.  
 Carbon dioxide (CAS 124-38-9) Listed.  
 Heptane (CAS 142-82-5) Listed.  
 Toluene (CAS 108-88-3) Listed.

**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Benzene (CAS 71-43-2) Listed.  
 Benzene, ethyl- (CAS 100-41-4) Listed.  
 Toluene (CAS 108-88-3) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Acetone (CAS 67-64-1) Listed.  
 Heptane (CAS 142-82-5) Listed.  
 Toluene (CAS 108-88-3) Listed.

**US - Louisiana Spill Reporting: Listed substance**

Acetone (CAS 67-64-1) Listed.  
 Heptane (CAS 142-82-5) Listed.  
 Toluene (CAS 108-88-3) Listed.

**US - Michigan Critical Materials Register: Parameter number**

Toluene (CAS 108-88-3) 00108-88-3 Listed.

**US - Minnesota Haz Subs: Listed substance**

Acetone (CAS 67-64-1) Listed.  
 Carbon dioxide (CAS 124-38-9) Listed.  
 Heptane (CAS 142-82-5) Listed.  
 Toluene (CAS 108-88-3) Listed.

**US - New Jersey RTK - Substances: Listed substance**

Acetone (CAS 67-64-1) Listed.  
 Carbon dioxide (CAS 124-38-9) Listed.  
 Heptane (CAS 142-82-5) Listed.  
 Toluene (CAS 108-88-3) Listed.

**US - New York Release Reporting: Hazardous Substances: Listed substance**

Acetone (CAS 67-64-1) Listed.  
 Toluene (CAS 108-88-3) Listed.

**US - North Carolina Toxic Air Pollutants: Listed substance**

Toluene (CAS 108-88-3) Listed.

**US - Texas Effects Screening Levels: Listed substance**

Acetone (CAS 67-64-1) Listed.  
 Carbon dioxide (CAS 124-38-9) Listed.  
 Heptane (CAS 142-82-5) Listed.  
 Toluene (CAS 108-88-3) Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Toluene (CAS 108-88-3) Listed.

**US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1) Listed.  
 Carbon dioxide (CAS 124-38-9) Listed.  
 Heptane (CAS 142-82-5) Listed.

Toluene (CAS 108-88-3)

Listed.

**US. Pennsylvania RTK - Hazardous Substances**

Acetone (CAS 67-64-1)

Listed.

Carbon dioxide (CAS 124-38-9)

Listed.

Heptane (CAS 142-82-5)

Listed.

Toluene (CAS 108-88-3)

Listed.

**US. Rhode Island RTK**

Acetone (CAS 67-64-1)

Listed.

Toluene (CAS 108-88-3)

Listed.

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**16. Other Information**

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

<b>HEALTH</b>	* 2
<b>FLAMMABILITY</b>	4
<b>PHYSICAL HAZARD</b>	1
<b>PERSONAL PROTECTION</b>	X



**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Issue date**

05-December-2014

**Effective date**

01-December-2014

**Expiry date**

01-December-2017

**Further information**

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

**Prepared by**

Nu-Calgon Technical Service Phone: (314) 469-7000

**Other information**

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).